

Datasheet N° : SECENV-CLEANFILL ADBLUE®

Product code : 308 131

Date : 03/2020

Page : 1/1

Version : V1

### Designation

Installed on the manlid of the tank, the Cleanfill 2" AdBlue® overfill prevention device is a piece of safety and environmental protection equipment intended for use on AdBlue® storage tanks.

The Cleanfill 2" AdBlue® was designed and developed for an exclusive AdBlue® application.

The Cleanfill 2" AdBlue® system is patented.

### Technical specifications

- Operating temperature range : -10°C to +35°C
- Stainless steel body
- High density polyethylen float
- Maximum flow rate : 40 m<sup>3</sup>/hr - 650 litres/minute
- Minimum flow rate : 2.4 m<sup>3</sup>/hr - 40 litres/minute
- Maximum pressure : 7 bar - 101 psi
- Minimum pressure : 150 mbar - 2.17 psi
- Re-opening time : less than one minute
- Fits to threaded BSP female sleeve-nut 2"

### + Product

- Very reliable and long working life
- Operational test on each unit
- Automatic operation
- Easily fitted or removed (without removing the man lid)
- Requires minimal space (optimises useful tank volume)
- Pressure or gravity filling
- Large window on the body for optimal flow
- Piston with grid and calibrates hole to prevent dirt

### Characteristics & standards

- Complies with EN 13616
- Complies with KIWA (certificate n° K 9152)
- Supplied with a declaration of conformity CE
- Type A : Effectiveness of overfill prevention devices – Pass
- Durability of effectiveness against temperature, chemical attack, fatigue and cycling – Pass

### Warranty

12 months provided fitting and operating instructions are observed.

