

Technical sheet N° : SECENV-09-2016

Product code : 308 130

Date : 09/2016

Page : 1/1

Version : V1

Designation

Fitted to the tank, the Cleanfill G 2"M overfill prevention device is a piece of safety and environmental protection equipment intended for use on domestic fuel and diesel storage tanks.

Application

Overfill prevention device, for use in installations for the transport/distribution/storage of gas/fuel intended for the supply of building, heating or cooling systems.

Technical specifications

- Maximum operating temperature : +50°C for domestic fuel or diesel with flashpoint equal or greater than 55°C
- Light high resistance anodized alloy body
- Maximum flow rate: 40 m³/h – 650 liters/minute
Minimum flow rate: 2,4 m³/h – 40 liters/minute
- Maximum pressure: 7 bar – 100 psi
Minimum pressure: 150 mbar – 2,17 psi
- Re-opening time : less than one minute
- Compact shape – fits within a 2" BSP diameter pipe (DN50)
- Suitable for direct or remote filling operation

+ Product

- Very reliable and long working life
- Operational test on every unit
- Automatic operation
- Easily fitted (without removing buffer)
- Requires minimal space (optimizes useful tank volume)
- Pressure or gravity filling

Characteristics & standards

- Complies with EN 13616
- Complies with KIWA (certificate n° K 9152)
- Supplied with a declaration of conformity CE
- Type A : Effectiveness of overfill prevention devices – Pass
- Durability of effectiveness against temperature, chemical attack, fatigue and cycling - Pass

Warranty

12 months provided fitting and operating instructions are observed.

