

TANK EQUIPMENT

Technical datasheet

Datasheet N° : Barrel pump G 2" – M 64x4

Product code : 107 402

BARREL PUMP G 2" with discharge hose SRL 355-955-24 l/min

Date : 11/2025

Page : 1/1

Version : Original

Designation

Pump housing with piston, hand lever and discharge spout intended for use with 60L / 200L / 220L containers, barrels, drums and tanks.

- Telescopic suction tube, adjustable in length (from 355 to 955 mm)
- Barrel screw coupling G 2" and barrel screw coupling M 64x4
- Discharge hose, 1500 mm, with steel discharge spout

Application

For oils up to SAE 50, diesel, petroleum, kerosene, glycerin and antifreeze undiluted

+ Product

- Hose holder
- Constant delivery rate for many years
- Completely dismountable - easy to clean
- Simple barrel installation by screw coupling
- Can be freely positioned in 30° increments
- Valuable sales package

Technical Specifications

- Delivery rate (l/stroke) : 0,40 l/stroke
- Delivery rate at 60 strokes/min : Env. 24L/min
- Pumping media : Oils up to SAE 50, diesel, petroleum, kerosene, glycerin and antifreeze undiluted
- Usage : 60/200/220L container, barrel, drum
- Discharge hose : Flexible 1500 mm with steel discharge spout
- Length, three-part suction pipe (mm): 355 to 955 mm
- Barrel screw coupling : barrel adapter G 2" M and M 64x4 M
- Materials of parts in contact with liquid
- Pump body : ABS + PA6
- Seals : FKM
- Metal pieces : galvanized steel, stainless steel, powder coated steel
- Dimensions (L x W x H) : 395 x 243 x 125 mm

Warranty

12 months provided fitting and operating instructions are observed.

	Weight Kg	Part no.
Barrel pump G 2" with discharge hose SRL 355-955-24 l/min	2,30	107 402

