

TANK EQUIPMENT

Technical datasheet

Datasheet N° : Barrel pump for AdBlue® G 2"

Product code : 107 403

Barrel pump for AdBlue® G 2" SRL 355-955-24 l/min

Date : 11/2025

Page : 1/1

Version : Original

Designation

Pump housing with piston, hand lever and discharge spout intended for use with 60L / 200L / 220L containers, barrels, drums and tanks.

- Telescopic suction tube, adjustable in length (from 355 to 955 mm)
- Barrel screw coupling G 2"
- Packed in single carton box

Application

For AdBlue®, urea, water, windshield washer fluid, antifreeze

+ Product

- Constant delivery rate for many years
- Completely dismountable - easy to clean
- Simple barrel installation by screw coupling
- Can be freely positioned
- Valuable sales package

Technical Specifications

- Delivery rate (l/stroke) : 0,40 l/stroke
- Delivery rate at 60 strokes/min : Env. 24L/min
- Pumping media : AdBlue®, urea, water, windshield washer fluid, antifreeze
- Usage : 60/200/220L container, barrel, Drum
- Discharge : Discharge spout
- Length, three-part suction pipe (mm): 355 to 955 mm
- Barrel screw coupling : Barrel adapter G 2"M
- Materials of parts in contact with liquid
- Pump body : ABS + PA6
- Seals : FKM + HNBR
- Dimensions (L x W x H) : 395 x 243 x 125 mm

Warranty

12 months provided fitting and operating instructions are observed.

	Weight Kg	Part no.
Barrel pump for AdBlue® G 2" SRL 355-955-24 l/min	1,70	107 403

