

Technical datasheet No. : SECENV-ANTIFREEZE PROGEL
Product code : 308 376

Date : 01/2017
Version : V1

Page : 1/1

Description

PROGEL DP SANITAIRE is a ready-to-use antifreeze up to -30°C formulated based on Mono Propylene Glycol, specifically developed in accordance with environmental legislation. It is designed to protect the liquid leak detection system FUITALARME 16 SC.R for double wall tanks.

Application

For double wall tanks containing fuels/automobile fuels, with **PROGEL DP SANITAIRE** antifreeze liquid in the interstitial space.

Properties

Fully inhibited against corrosion, **PROGEL DP SANITAIRE** antifreeze ensures total protection of the electrodes on leak detectors. **PROGEL DP SANITAIRE** antifreeze is non-flammable, stable in time, compatible with hard water. It is perfectly neutral to paints or coatings.

Use / Concentrations

Perfectly soluble in water, the concentration of **PROGEL DP SANITAIRE** antifreeze depends on the degree of protection desired.

FREEZING POINT	% VOLUME OF "PROGEL DP SANITAIRE"
-10°C	28%
-15°C	37%
-20°C	43%
-25°C	47%
-30°C	50%

PROGEL DP SANITAIRE is not subject to any labeling information.

Characteristics

- Physical state : liquid
- Colour : rose
- Density (pure product at 20°C) : $1,060 \pm 0,010$
- pH value (pure product) : $9,5 \pm 0,5$

Warranty

12 months provided fitting and operating instructions are observed.

