

LEAK DETECTOR

Technical datasheet

Technical datasheet No.: SECENV_LWG2000

Product code: 308 380 / 308 384

Leak alarm unit LWG 2000 with probe

Date : 03/2018

Page : 1/1

Designation

Leak detection system consisting of a control unit with visual/audible alarm and a probe.

Application

- For storage rooms, manholes, drip pans and pumps
- Suitable for the following media : waste oil, diesel fuel, FAME, fuel oil, fuel oil bio, heavy heating oil, industrial oil, vegetable oil, water, water-oil mixtures, urea solution, non-flammable liquids with a flash point > 55 °C

Operating

- Triggers a visual/audible alarm when the probe comes into contact with liquid

+ Product

- Control unit with visual/audible alarm
- Test and Acknowledge buttons
- One relay output

Technical specifications

Display unit

- Supply voltage : 230 V AC ; 50-60 Hz
- Power consumption : 2.5 VA
- Voltage tolerance : +10% / -15%
- Alarm sound level : ≥ 70 dB(A)
- Dimensions (H x W x D) : 120 x 120 x 50 mm
- Ambient temperature : -20°C to +60°C
- Degree of protection : IP 30 acc. to EN 60529
- Housing : Polyester

Probe

- Voltage : 12 V DC
- Cable : 2 x 0,5 mm²
- Cable length : 2 m (supplied with item no. 308 380)
5 m (supplied with item no. 308 384)
- Cable extension : 100 m max. (with cable 2 x Ø 1,5 mm²)
- Probe material : Stainless steel 1.4301
- Standards : Class III
NF EN 13160-1
NF EN 13160-4

Item reference

- Leak alarm LWG 2000 with 2 m cable (item no. 308 380)
- Leak alarm LWG 2000 with 5 m cable (item no. 308 384)

Warranty

12 months provided fitting and operating instructions are observed.

